





# SPOTY ROUND 4



LED Einsatz 7W/10W




LED Einsatz 7W Warmdim



LED Einsatz 13W Warmdim  
LED Einsatz Tunable White




B schwarz



W weiss

Artikelnummer	Farbe	DALI PUSH	Leistung	Lichtfarbe	Lichtstrom	Primär	Sekundär	Winkel	CRI
LW25-R7-07-2700-1-	1	2	7W	2700K	840lm	230V	180mA	30°	CRI>90
LW25-R7-07-3000-1-	1	2	7W	3000K	879lm	230V	180mA	30°	CRI>90
LW25-R7-07-4000-1-	1	2	7W	4000K	905lm	230V	180mA	30°	CRI>90
LW25-R7-10-2700-1-	1	2	10W	2700K	1199lm	230V	250mA	30°	CRI>90
LW25-R7-10-3000-1-	1	2	10W	3000K	1255lm	230V	250mA	30°	CRI>90
LW25-R7-10-4000-1-	1	2	10W	4000K	1305lm	230V	250mA	30°	CRI>90
LW25-R7-07-2200-1-	1	2	7W	1800K - 3000K	530lm	230V	350mA	30°	CRI>90
LW25-R7-13-2200-1-	1	2	13W	1800K - 3000K	900lm	230V	350mA	30°	CRI>90
LW25-R7-10-TW-1-	1	2	10W	2700K - 5700K	900-930lm	230V	350mA	30°	CRI>90

- 1 B schwarz
- 1 W weiss
- 2 D DALI/PUSH



NEU 10 LED Einsatz 7W/10W



07 LED Einsatz 7W Warmdim



13 LED Einsatz 13W Warmdim




TW LED Einsatz Tunable White



PP250023B Blendschutz




PP250019 Linse 15°



PP250016 Linse 50°



PP250015 Opal



PP250014 Wabenraster