

Product family

WALLY TECTUM

Surface-mounted luminaires including reflectors from the WALLWASHER series with Bartenbach technology have an asymmetrical radiation characteristics with complex surface microfacet technology, the perfect wall lighting begins directly at the edge of the ceiling and guarantees an absolutely even surface illumination, housing made of sheet steel, LED circuit board can be changed (screwed), tunable white lighting solutions on request, including integrated converter (DALI dimmable)



WALLY TECTUM

CHARACTERISTIC








- ① surface-mounted luminaire WALLY TECTUM in 3 lengths available (920/ 1220/ 1520mm)
- ① with 5 units WALLWASHER with 60mm distance 60mm
- ① light color: 2700K, 3000K or 4000K
- ① equipped with HIGH-Power LED
- ① asymmetric wallwasher 2x45° (longitudinal) and 85° (lateral)
- ① housing: black RAL9005, silver grey RAL9006, white RAL9016 or special color on request
- ① degree of protection: IP20
- ① glare-free lighting (>UGR 19)
- ① TW Tunable White on request
- ① incl. converter (DALI dimmable)

WALLY TECTUM

Watt Total:	40W		
Length:	920mm (15x Wallwasher)		
Kelvin (CCT):	2700K	3000K	4000K
Net lumens:	2900lm	3060lm	3320lm

Watt Total:	53W		
Length:	1220mm (20x Wallwasher)		
Kelvin (CCT):	2700K	3000K	4000K
Net lumens:	4350lm	4590lm	4980lm

Watt Total:	66W		
Length:	1520mm (25x Wallwasher)		
Kelvin (CCT):	2700K	3000K	4000K
Net lumens:	5800lm	6120lm	6640lm

Efficiency:	82%		
CRI:	>90Ra		
Angle:	2x45° (lengthways), 85° (sideways)		
Life expectancy:	50.000h, L80B20, ta=25°C		
Voltage:	100 ~ 230V AC/600mA		
Others:	LED       		

Product overview:

Types:



WALLY TECTUM 09



WALLY TECTUM 12



WALLY TECTUM 15

Reflector:

2x 45°/85°


Light colors:



2700K superwarm white



3000K warm white



4000K neutral white


Housing colors:



black RAL9005



silver grey RAL9006




white RAL9016

Article overview:


item number	① length	reflector	② kelvin	③ color	④ converter
LW-WW-T①-②-③-④	» 09 « 920mm	15	» SW « 2700K	» B « ● RAL9005	» D « incl. DALI
	» 12 « 1220mm	20	» WW « 3000K	» S « ● RAL9006	
	» 15 « 1520mm	25	» NW « 4000K	» W « ○ RAL9016	

Drawings:


WALLY TECTUM 09




WALLY TECTUM 12



WALLY TECTUM 15



Light distribution:



Wallwasher