

Product family

STANDARD STRIPES IP65

Flexible LED stripe with self-adhesive back, lifespan up to 50,000 hours, excl. converter / control unit, excl. cooling profile, max. length per feed: 5m, only available in full rolls



CHARACTERISTIC

- 4 wattages to choose from
- color temperature 2700K, 3000K, 4000K, RGB + W
- degree of protection: IP65
- protection class: 3
- CRI > 95Ra
- CRI > 80Ra (RGB + W)
- output voltage 24V DC

SPECIAL FEATURE

- degree of protection IP65
- IP65 stripes only available in whole 5m rolls



Product overview:

Types:



LW-FLEX-13 STANDARD
IP65



LW-FLEX-21 STANDARD
IP65



LW-FLEX-26 STANDARD
IP65



LW-FLEX-RGB+W
IP65


Light Color:



2700K super warm white



3000K warm white



4000K neutral white



RGB+W (3000K)

Technical information:

LW-FLEX-13 STANDARD IP65

LED:	2835 High Brightness SMD LED		
Total watt:	13W/ Meter		
Net lumen:	1170lm/m	1230lm/m	1290lm/m
Kelvin (CCT):	2700K	3000K	4000K
Protection:	IP65		
CRI:	>95Ra		
Number of LEDs:	60 LEDs/ Meter		
Life expectancy:	50.000 Hours		
Voltage:	24V DC		

LW-FLEX-21 STANDARD IP65

LED:	2835 High Brightness SMD LED		
Total watt:	21W/ Meter		
Net lumen:	1872lm/m	1968lm/m	2064lm/m
Kelvin (CCT):	2700K	3000K	4000K
Protection:	IP65		
CRI:	>95Ra		
Number of LEDs:	96 LEDs/ Meter		
Life expectancy:	50.000 Hours		
Voltage:	24V DC		

LA-FLEX-26 PREMIUM IP65


LED:	2835 High Brightness SMD LED		
Total watt:	26W/ Meter		
Net lumen:	2340lm/m	2460lm/m	2580lm/m
Kelvin (CCT):	2700K	3000K	4000K
Protection:	IP65		
CRI:	>95Ra		
Number of LEDs:	120 LEDs/ Meter		
Life expectancy:	50.000 Hours		
Voltage:	24V DC		

LW-FLEX-RGB+W IP65


LED:	5050 High Brightness SMD LED			
Total watt:	18W/ Meter			
Net lumen:	88lm/m	326lm/m	81lm/m	288lm/m
Kelvin (CCT):	Rot	Grün	Blau	White
Protection:	IP65			
CRI:	>80Ra			
Number of LEDs:	60 LEDs/ Meter			
Life expectancy:	50.000 Hours			
Voltage:	24V DC			

Drawings:


LW-FLEX-13 STANDARD




LW-FLEX-21 STANDARD



LW-FLEX-26 STANDARD



LW-FLEX-RGB+W



Article overview:

item number	product name	W	K	lm	IP	CRI	...
LW24-SW-13-IP65	LW-FLEX-13 STANDARD	13W/m	2700K	1170lm/m	IP65	95Ra	60/m
LW24-WW-13-IP65	LW-FLEX-13 STANDARD	13W/m	3000K	1230lm/m	IP65	95Ra	60/m
LW24-NW-13-IP65	LW-FLEX-13 STANDARD	13W/m	4000K	1290lm/m	IP65	95Ra	60/m
LW24-SW-21-IP65	LW-FLEX-21 STANDARD	21W/m	2700K	1872lm/m	IP65	95Ra	96/m
LW24-WW-21-IP65	LW-FLEX-21 STANDARD	21W/m	3000K	1968lm/m	IP65	95Ra	96/m
LW24-NW-21-IP65	LW-FLEX-21 STANDARD	21W/m	4000K	2064lm/m	IP65	95Ra	96/m
LW24-SW-26-IP65	LW-FLEX-26 STANDARD	26W/m	2700K	2340lm/m	IP65	95Ra	120/m
LW24-WW-26-IP65	LW-FLEX-26 STANDARD	26W/m	3000K	2460lm/m	IP65	95Ra	120/m
LW24-NW-26-IP65	LW-FLEX-26 STANDARD	26W/m	4000K	2580lm/m	IP65	95Ra	120/m
LW24-RGBW-18-IP65	LW-FLEX-RGB+W	18W/m	RGB+W 3000K	R = 88lm/m G = 326lm/m B = 81lm/m W = 288lm/m	IP65	80Ra	60/m

